

RULE CHANGES

MULTI CLASSES

- Added driver protection-From the rear area of the Halo bar, on the driver side extending down ward and attaching either to the top door bar or the vertical cage member toward the lower area a bar will need to be installed. Highly recommend for 2023 mandatory 2024 Details to follow.
- Air cleaner element height – cannot exceed the max height of hood scoop height measurement as allowed by each class.
- Break away right rear T-bar- Right rear corner deck support. Highly recommended for 2023 mandatory for 2024 Late Model, Modified, Super Stock, Midwest Modified and Mod-4 [Dia. To follow]
- Drive shaft hoops must make a complete 360* hoop around drive shaft.
- Seat belts Min. width 2"
- Upon technical inspection if a non-stamped and or non-stickered wheel is discovered The driver will be penalized 2 finishing positions.
- Allow the Eagle 1 pc rear main seal steel crank shaft P/N 435334805700 Super Stocks Midwest Modifieds and Street Stocks.
- Electric fans not allowed. In all classes except Hornet.

Late Models

- Deck height 40" no tolerance. Measured in the center of rear deck.

Modified

- Tooled steel lifters are allowed in Modified concept engine package.
- .083 thick door bars are allowed.
- A total of a 2 ½" combined rubber or fiber bump stops or packers or washers allowed on the R.F. shock. No spring bumps.

Super Stock

- Allow Dart Head P/N 10024360.
- Steel swedge tubes with steel Heim joints are allowed. Inner and outer heim joints.

Midwest Modified

- REMINDER- Carbon fiber drive shafts are legal. MUST BE WHITE
- .083 thick door bars are allowed.
- Schrader style valves/ gas fill ports on shocks are allowed.

Street Stock

- Back of trunk must be level or lower than front of trunk. With a max rear trunk height of 43"
- Schrader style valves/ gas fill ports on shocks are allowed.
- Allow removable shims and adjustable spring cups. [non-welded].
- Allow bead locks on all 4 wheels.

- Camaro and Mustang noses are legal. [must use correct p/n] Rear roof post/C pillar must Match body claimed. Not what nose is.

Mod-4

- Allow roller cam/ roller cam followers. Same lift as current rule.
- Allow up to 1" aluminum wheel spacer on any corner of car.

Hornet

- Battery may only be under hood or in trunk area (not within cockpit area) if battery in trunk – rear firewall must be enclosed.
- ABS brakes must be disabled.
- 2" max. exhaust size for all years, models and makes.
- No progressive springs.
- All cars must have front sway bar. [Must be hooked up].
- Claim \$2500 or \$1000 exchange.
- Must have stock wiring harness. Plugs not used can be cut off.
- Rear of car can be reinforced. [Rusted out rear frame or unibody frame under back
- Of car can be reinforced to support trunk area and back bumper only. No other bracing or reinforcing allowed.]
- Allow 1" inspection hole in bell housing